

Enardo™ Flame and Detonation Arrestor Selection Guide

Standard Flame Arrestor Selection Criteria

PARAMETERS	END-OF-LINE FVFA AND VSFA	IN-LINE (STANDARD) ENARDO 7 SERIES, HP AND IL	IN-LINE HP DEFLAGRATION ENARDO 8 SERIES	DETONATION ARRESTOR DFA
NEC Group "D" or IEC Group IIA Gases				
Maximum length of pipe between the arrestor and the ignition source without bends.	(Mounted on end of pipe)	20 ft / 6 m	60 ft / 18 m	Unlimited
Maximum length of pipe between the arrestor and ignition source with 1 to 90° bend.	(Mounted on end of pipe)	20 ft / 6 m	60 ft / 18 m	Unlimited
Maximum length of pipe between the arrestor and the ignition source with multiple bends.	(Mounted on end of pipe)	Not Recommended with Multiple Bends	Not Recommended with Multiple Bends	Unlimited
Flame Stabilization at stoichiometric mixture and ambient temperature not to exceed at 140°F / 60°C. ⁽¹⁾	5 minutes	5 minutes 30 minutes (Factory Mutual Approved units)	15 minutes	2 hours (concentric only)
Operating Pressure	Atmospheric	15.4 psia / 106 kPa	19.7 psia / 134 kPa	Concentric: 3 to 12 in. (22.7 psia) / 50 to 300 mm (157 kPa) Concentric: 2 and 14 to 20 in. (20.7 psia) / 350 to 500 mm (143 kPa)
NEC Group "C" or IEC Group IIB3 Gases				
Maximum length of pipe between the arrestor and the ignition source without bends.	(Mounted on end of pipe)	6 ft / 2 m (open ended pipe)	35 ft / 10.6 m	Unlimited
Maximum length of pipe between the arrestor and ignition source with 1 to 90° bend.	(Mounted on end of pipe)	6 ft / 2 m (open ended pipe)	35 ft / 10.6 m	Unlimited
Maximum length of pipe between the arrestor and the ignition source with multiple bends.	(Mounted on end of pipe)	Not Recommended with Multiple Bends	Not Recommended with Multiple Bends	Unlimited
Flame Stabilization at stoichiometric mixture and ambient temperature not to exceed at 140°F / 60°C. ⁽¹⁾	5 minutes (minimum)	5 minutes (minimum)	15 minutes	15 minutes
Operating Pressure	Atmospheric	15.4 psia / 106 kPa	16.7 psia / 115 kPa	Concentric: 2 to 20 in. (20.7 psia) / 50 to 500 mm (143 kPa) Eccentric: 3 to 20 in. (18.7 psia) / 75 to 500 mm (129 kPa)
NEC Group "B" or IEC Group IIC Gases (Except Acetylene)				
Maximum length of pipe between the arrestor and the ignition source without bends.	(Mounted on end of pipe)	4 ft / 1.2 m (open ended pipe)	15 ft / 4.5 m	Unlimited
Maximum length of pipe between the arrestor and ignition source with 1 to 90° bend.	(Mounted on end of pipe)	Not Recommended with a Bend	15 ft / 4.5 m	Unlimited
Maximum length of pipe between the arrestor and the ignition source with multiple bends.	(Mounted on end of pipe)	Not Recommended with Multiple Bends	Not Recommended with Multiple Bends	Unlimited
Flame Stabilization at stoichiometric mixture and ambient temperature not to exceed at 140°F / 60°C. ⁽¹⁾	2 minutes	2 minutes	15 minutes	15 minutes
Operating Pressure	Atmospheric	15.4 psia / 106 kPa	16.7 psia / 115 kPa	Concentric: 2 to 6 in. (17.7 psia) / 50 to 150 mm (122 kPa)
1. Unlimited burning should not be allowed in any flame arrestor regardless of its burn time rating. We recommend the use of flame sensors, along with an appropriate means of extinguishing the fire, in any situation where a stabilized burn may occur.				

Enardo™ Flame and Detonation Arrestor Selection Guide

ATEX Certified Flame Arrestor Selection Criteria

PARAMETERS	END-OF-LINE FVFA	IN-LINE (STANDARD) ENARDO 7 SERIES, HP AND IL	DETONATION ARRESTOR DFA
IEC Group IIA Gases or NEC Group "D"			
Maximum length of pipe between the arrestor and the ignition source.	(Mounted on end of pipe)	2 in. to 6.5 ft / 50 mm to 2 m 3 in. to 7.5 ft / 75 mm to 2.3 m 4 in. to 10 ft / 100 mm to 3 m 6 in. to 13.1 ft / 150 mm to 4 m 8 in. to 13.3 ft / 200 mm to 4 m 10 in. to 16.6 ft / 250 mm to 5 m 12 in. to 19.7 ft / 300 mm to 6 m	2 to 12 in. / 50 to 300 mm Unrestricted (Designed for Unstable Detonations)
Flame Stabilization at stoichiometric mixture and ambient temperature not to exceed at 140°F / 60°C.	Short Time Burn Rating	Short Time Burn Rating	Short Time Burn Rating
Operating Pressure	Atmospheric	15.95 psia / 110 kPa	2 to 6 in. (17.7 psia) / 50 to 150 mm (122 kPa) 8 to 12 in. (16.9 psia) / 200 to 300 mm (116.5 kPa)
IEC Group IIB3 Gases or NEC Group "C"			
Maximum length of pipe between the arrestor and the ignition source.	(Mounted on end of pipe)	2 in. to 8.3 ft / 50 mm to 2.5 m 3 in. to 12.5 ft / 75 mm to 3.8 m 4 in. to 16.6 ft / 100 mm to 5 m 6 in. to 25 ft / 150 mm to 7.6 m 8 in. to 33.3 ft / 200 mm to 10.16 m 10 in. to 39.3 ft / 250 mm to 12 m 12 in. to 39.4 ft / 300 mm to 12 m	2 to 12 in. / 50 to 300 mm Unrestricted (Designed for Unstable Detonations)
Flame Stabilization at stoichiometric mixture and ambient temperature not to exceed at 140°F / 60°C.	Short Time Burn Rating	Short Time Burn Rating	Short Time Burn Rating
Operating Pressure	Atmospheric	15.95 psia / 110 kPa	17.2 psia / 118.3 kPa

Emerson Automation Solutions Regulator Technologies

Americas

T +1 800 558 5853
T +1 972 548 3574

✉ webadmin.regulators@emerson.com

🔍 Enardo.com

Europe

T +39 051 419 0611

📘 Facebook.com/EmersonAutomationSolutions

Asia Pacific

T +65 6770 8337

🌐 LinkedIn.com/company/emerson-automation-solutions

🐦 Twitter.com/emr_automation

Middle East / Africa

T +971 4811 8100

