# Re-engineered for increased durability and simplified maintenance



# Type N550 is Now Type N551

The trusted Type N550 shutoff valve is widely known by the LPG industry to provide maximum full-port flow performance, reliable shut-off and with low-cost of ownership. Improving upon those proven strengths in order to meet the increasing service demands, the Type N551 has been re-engineered to provide enhanced gland and sealing robustness and simplified maintenance.

# **Type N551 Emergency Shutoff Valve**

The Type N551 emergency shutoff valve is intended for in-line use in LPG or Anhydrous Ammonia NH<sub>3</sub> service. The valve may be installed on either end of the transfer hoses and typically where the hose connects the bulk plant piping to the bobtail, transport or tank car. The Type N551 provides a quick way of shutting off gas flow in the event of a hose rupture.

TYPE N551 EMERGENCY SHUTOFF VALVES					
Туре	Body Size, FNPT	Propane Flow at 2 psi / 0.14 bar Differential, GPM / I/min	Maximum Inlet Pressure	Maximum Temperature Capability	
N551-10	1-1/4	150 / 568			
N551-16	2	295 / 1117	400 psig / 27.6 bar	160°F / 71°C*	
N551-24	3	850 / 3127			

OPTIONS				
Seat Discs	Operation Methods			
Standard disc and O-ring material is Nitrile (NBR)	Manual/Cable pull standard (add P164B)			
Viton® and Kalrez® available	Air close P327D actuator			
	Air open-close P539A actuator			

<sup>\*</sup>All seats and seals use UL® tested materials rated for -40°F / -40°C. UL® is a mark owned by Underwriters Laboratories. Viton® and Kalrez® are marks owned by E.I. du Pont de Nemours and Co.



# PERFORMANCE AND VALUE

Emerson offers Fisher™ Snappy Joe™ Emergency Shutoff Valves (ESV) that are reliably serving generations of customers in the LPG Industry. The original shutoff valve is preferred for its:

- Rugged construction
- Full-port flow performance
- Range of material options
- Integral 212°F thermal fuse link
- Reliable release latch
- · Low cost of ownership

#### **FEATURES**


- Ease of maintenance
- · Enhanced packing design
- Simplified gland construction

#### **APPLICATIONS**

- Bulk plant
- Rail car
- Specialty gases

## FLOW PERFORMANCE

Type N551 is designed to give the maximum full-port flow available for a given piping diameter.



#### **BENEFITS**

- Poppet and Shaft remain connected to prevent lost time and potential dissassembly from piping system during gland maintenance
- Increased cycle life and improved sealing performance at cold temperatures
- Elimination of nuisance leakage and shaft binding if retainer is torqued unevenly

#### ENHANCED PACKING DESIGN


The gland packing of Type N551 has been re-designed to provide an improved seal for increased cycle life.

#### **FEATURES**

- Superior gland seal geometry with captured O-ring seal (1)
- Optimized polytetrafluoroethylene (PTFE) Chevron packing (2)
- New gland design permits a wider torque range on the retainer bolts for a consistent seal and smooth, dependable valve action (3)

## FIELD PROVEN FEATURES

- Stainless steel trim parts
- · Heavy duty spring to close design
- UL®-Listed design



Re-designed Gland, Retainer and main gland external O-ring seal improve cycle life and seal performance.

### **ACTUATOR CONTROL PACKAGE**

### The Type P539A actuator is:

Designed for enhanced service life and exceeds UL's cycle testing requirements.



# **SERVICEABILITY**

Convenient bolt gland design for easy inspection and service. Type N551 is easily serviced with few parts.



# SUPERIOR SERVICE AND SUPPORT

Emerson's industry leading service and support offers a complete line of LPG equipment with a worldwide distribution network. Our experienced sales and support teams consist of more than 2000 technical experts available to serve you from nearly 200 offices worldwide. Contact Emerson to learn more about our services.

UL® is a mark owned by Underwriters Laboratories.

#### **Emerson Automation Solutions**

#### **Americas**

T +1 800 558 5853 T+19725483574

# Europe

T+39 051 419 0611

#### Asia Pacific T+65 6777 8211

#### Middle East / Africa T+971 4811 8100

- webadmin.regulators@emerson.com
- Fisher.com
- Facebook.com/EmersonAutomationSolutions
- in LinkedIn.com/company/emerson-automation-solutions
- Twitter.com/emr\_automation

